



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0592 10" x 18" Metal Cutting Bandsaw



MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)

- Powerful 2HP motor with variable speed control ranging from 98 to 394 feet per minute.
- Swivel head ranges from 45° right, to 60° left with quick positioning vise.
- Smooth hydraulic downfeed control.
- Rapidly adjustable blade guide system and heavy-duty ball bearings in the blade wheels.
- Built in coolant pump and reservoir with convenient wash down hose.
- Excellent industrial quality machine made in an ISO 9001 rated factory.

The Model G0592 10" x 18" Metal Cutting Bandsaw is available for \$4,295.00. As with all Grizzly products, the Model G0592 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0592 METAL CUTTING BANDSAW 10" X 18"

Product Dimensions:

Weight..... 858 lbs.
 Length/Width/Height..... 72-1/2 x 32 x 58 in.
 Foot Print (Length/Width)..... 28-1/2 x 45 in.

Shipping Dimensions:

Type..... Wood Slat Crate
 Content..... Machine
 Weight..... 967 lbs.
 Length/Width/Height..... 79 x 36 x 79 in.

Electrical:

Minimum Circuit Size..... 60 amp
 Switch..... On/Off Located in Saw Bow
 Switch Voltage..... 220V
 Cord Length..... 6 ft.
 Cord Gauge..... 14 gauge
 Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
 Horsepower..... 2 HP
 Voltage..... 110/220V
 Prewired..... 220V
 Phase..... Single
 Amps..... 30/15A
 Speed..... 1725 RPM
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer V-Belt
 Bearings..... Shielded and Lubricated

Main Specifications:

Operation Info

Blade Speeds..... 98 - 394 FPM
 Std. Blade Len..... 132 in.
 Head Swivel..... Right 45, Left 60 deg.

Cutting Capacities

Angle Cuts.....	Right 45, Left 60 deg.
Vise Jaw Depth.....	7-1/2 in.
Vise Jaw Height.....	5 in.
Max. Capacity Rect. Height At 90D.....	9-1/2 in.
Max. Capacity Rect. Width At 90D.....	18 in.
Max. Capacity Rnd. At 90D.....	10 in.
Max. Capacity Rect. Height At 45D.....	10 in.
Max. Capacity Rect. Height At 30D.....	10 in.
Max. Capacity Rect. Width At 30D.....	14 in.
Max. Capacity Rnd. At 30D.....	10 in.
Max. Capacity Rect. Width At 45D.....	11 in.
Max. Capacity Rnd. At 45D.....	10 in.
Max. Capacity Rect. Height At 60D.....	5 in.
Max. Capacity Rect. Width At 60D.....	8 in.
Max. Capacity Rnd. At 60D.....	8 in.

Construction

Table Construction.....	Cast Iron
Wheel Construction Upper.....	Cast Iron
Wheel Construction Lower.....	Cast Iron
Body Construction.....	Formed Steel
Base Construction.....	Cast Iron
Stand Construction.....	Formed Steel
Wheel Cover Construction.....	Pre-formed Steel
Paint.....	Epoxy

Other

Blade Guides Upper.....	Ball Bearing
Blade Guides Lower.....	Ball Bearing
Coolant Cap.....	1 liter

Table Info

Floor To Cutting Area Height.....	20 in.
-----------------------------------	--------

Other Specifications:

Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	Grizzly ID Label
Assembly Time	90 minutes

Features:

- Coolant Pump
- Blade Speed Chart
- Variable Speed
- Quick Positioning Vise
- Adjustable Hydraulic Downfeed
- Automatic Shut-off