



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0609X 12" X 83¹/₂" Parallelogram Jointer with Spiral Cutterhead



Pre-installed at the factory, the indexable insert spiral cutterhead makes Grizzly's 12" jointer absolutely unbeatable and does an incredible job on all types of woods, particularly figured woods that are normally prone to tearout.

MACHINE HIGHLIGHTS (see *Machine Data Sheet for full specifications*)

- 3 HP, 220V, Single-Phase.
- Parallelogram table adjustment system.
- Convenient pedestal mounted switch.
- Precision ground cast iron table.
- Four-sided solid carbide inserts for spiral cutterhead are made in Germany.
- Industrial duty construction with thick castings and heavy gauge steel—weighs 884 lbs!

The Model G0609X is available for \$2,250.00. As with all Grizzly products, this machine is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0609X 12" JOINTER W/ SPIRAL CUTTERHEAD

Product Dimensions:

Weight..... 884 lbs.
 Length/Width/Height..... 84 x 33 x 43-1/2 in.
 Foot Print (Length/Width)..... 44-1/4 x 18 in.

Shipping Dimensions:

Type..... Wood Crate
 Content..... Machine
 Weight..... 1045 lbs.
 Length/Width/Height..... 88-3/8 x 29-3/4 x 40-1/2 in.

Electrical:

Minimum Circuit Size..... 20 amp
 Switch..... Magnetic with Thermal Overload Protection
 Switch Voltage..... 220V
 Cord Length..... 5 ft.
 Cord Gauge..... 12 guage
 Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
 Horsepower..... 3 HP
 Voltage..... 220V
 Prewired..... 220V
 Phase..... Single
 Amps..... 15A
 Speed..... 3450 RPM
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer V-Belt
 Bearings..... Shielded and Lubricated

Main Specifications:

Fence Information

Fence Length..... 46-3/4 in.
 Fence Width..... 1-1/2 in.
 Fence Height..... 5-3/8 in.
 Fence Stops..... 45 and 90 deg.

Cutting Capacities

Bevel Jointing..... 90-45 deg.
 Maximum Width of Cut..... 12 in.
 Maximum Depth of Cut..... 1/8 in.
 Maximum Rabbeting Depth..... 3/4 in.
 Number of Cuts Per Minute..... 19800

Cutterhead Information

Cutterhead Type.....	Spiral
Cutterhead Diameter.....	3-7/8 in.
Number of Cutter Spirals.....	4
Number of Indexable Cutters.....	60
Cutter Insert Type.....	Indexable
Cutter Insert Length.....	14 mm
Cutter Insert Width.....	14 mm
Cutter Insert Thickness.....	2 mm
Cutterhead Speed.....	4950 RPM

Table Information

Table Length.....	83-1/2 in.
Table Width.....	12-3/4 in.
Table Thickness.....	1-7/8 - 3-1/4 in.
Floor to Table Height.....	31-11/16 in.
Table Adjustment Type.....	Handwheel
Table Movement Type.....	Parallelogram

Construction

Base Construction.....	Cast Iron
Body Assembly Construction.....	Cast Iron
Cabinet Construction.....	Cast Iron
Fence Assembly Construction.....	Cast Iron
Guard Construction.....	Moulded Aluminum
Table Construction.....	Precision Ground Cast Iron
Parallelogram.....	Yes
Paint.....	Powder Coated

Other Information

Number of Dust Ports.....	1
Dust Port Size.....	5 in.

Other Specifications:

Country Of Origin	China
Warranty	1 Year
Serial Number Location	Data Label on Front of Cabinet
Assembly Time	45 minutes

Features:

- Parallelogram Beds
- Top Mount Switch Controls
- 5 3/8" Tall Fence
- Included Push Blocks
- 5" Dust Port
- Spiral Cutterhead with German-Made Indexable Carbide Inserts